Supporting Information

"Free" Volume Expansion and Formation Enthalpy of Defects as Key Parameters Tuning the Oxide Ionic Conductivity in Derivatives of β-La₂Mo₂O₉

Gwenaël CORBEL^{1*}, Ania SELMI¹, Emmanuelle SUARD² and Philippe LACORRE¹

¹ LUNAM, Université du Maine, Institut des Molécules et Matériaux du Mans, UMR-6283 CNRS, Avenue Olivier Messiaen, 72085 Le Mans Cedex 9, France

² Institut Laue-Langevin, BP 156, 38042 Grenoble Cedex 9, France

* To whom correspondence should be addressed LUNAM Université, Université du Maine, Institut des Molécules et Matériaux du Mans UMR-6283 CNRS, Avenue Olivier Messiaen, 72085 Le Mans Cedex 9, France. Tel : +33 (0)2 43 83 26 48 FAX : +33 (0)2 43 83 35 06 E-mail : gwenael.corbel@univ-lemans.fr <u>1. Thermal evolution of O1-cation bond lengths, of the distance between O1 and the</u> [(La/Ba)₃] base and of bond angles within the [O1(La/Ba)₃Mo] anti-tetrahedral basic unit as a function of temperature in β -La_{1.85}Ba_{0.15}Mo₂O_{8.925}.



Figure S1

2. Dependence of the electrical conductivity at high temperature fitted with the Vogel-Tammann-Fulcher (VTF) model.



Figure S2 : Temperature dependence of the electrical conductivity of β -La_{1.7}Bi_{0.3}Mo₂O₉ (black and open circles) and of β -La_{1.85}Ba_{0.15}Mo₂O_{8.925} (black and open circles) compared to that of La₂Mo₂O₉ (pellet sintered 3h at 1000°C, relative density 96(1)% of theoretical density, solid red line) and to that of 8mol% yttria stabilized zirconia (solid blue line, from reference ³). The conductivity plot was fitted with a conventional Arrhenius law in the linear part at low temperature (dashed black line) and with the empirical VTF model when departure from linearity is observed at higher temperature (solid black line). At the bottom, plot of the first derivative of the conduction with respect to temperature is shown (black circles).

Composition	Sintering Conditions	Relative density (%)	Arrhenius regime			VTF regime			
			$\sigma T = \sigma_0 \exp \left[-E_a/RT\right]$			$\sigma T = \sigma_0 \exp \left[-B/R(T-T_0)\right]$			
			$\log(\sigma_0)$	E_a	r^2	$\log(\sigma_0)$	В	T_0	r^2
			$(S.K.cm^{-1})$	(eV)	1	$(S.K.cm^{-1})$	(eV)	(°C)	1
$\beta - La_{1.7}Bi_{0.3}Mo_2O_9$	5h 875°C	98(1)	7.74	1.27	0.9999	3.84	0.21	246	0.9996
β -La _{1.85} Ba _{0.15} Mo ₂ O _{8.925}	12h 1000°C	94(2)	7.90	1.31	0.9999	5.24	0.39	144	0.9997

 $\label{eq:sigma} \begin{array}{l} \textbf{Table S1}: Sintering \ conditions, \ relative \ density \ and \ parameters \ of \ the \ Arrhenius \ and \ the \ Vogel-Tammann-Fulcher \ (VTF) \ -type \ laws \ determined \ for \ \beta-La_{1.7}Bi_{0.3}Mo_2O_9 \ and \ \beta-La_{1.85}Ba_{0.15}Mo_2O_{8.925} \end{array}$

3. Comparison of the temperature dependences of the "free" cell volumes $V_{\underline{F}}$ deduced from the analysis of neutron diffraction patterns and of complex impedance spectra for β -La_{1.85}Ba_{0.15}Mo₂O_{8.925} and β -La_{1.7}Bi_{0.3}Mo₂O₉ compounds.



Figure S3

4. Comparison of the fraction of non-occupied volume in β -La_{1.7}Bi_{0.3}Mo₂O₉ and in β -La_{1.85}Ba_{0.15}Mo₂O_{8.925} above 400°C to that determined in β -La₂Mo₂O₉ at 670°C.



Figure S4